

# IPN-ISDCN6206

**Full HD**  
1920x1080

## 1080P IR IP SPEED DOME



### Features:

- 2MP HD intelligent IR network high speed dome camera
- H.264/MJPEG
- 1080P, 20X optical zoom, F=4.45mm~89mm
- Manual control speed: 0.1-150°/S, preset speed: 180°/S
- Horizontal continuous rotate 360 °, 90 ° vertically auto rotation
- Adopt high efficiency infrared array, low power consumption, IR irradiation distance 100m
- 256 preset, 4 pattern, 8 cruise
- Lighting-proof, IP66, DC12V, Standard wall mounting bracket

## Specifications:

MODEL	IPN-ISDCN6206
CAMERA	
Pick-up device	1/2.9" 2.43Mega CMOS Sensor, Canon lens
Effective Pixels	2.1 Megapixel
Video Output	1080p/30, 1080p/25, 720p/30, 720p/25
Min. Illumination	0.5 LUX (F1.6, ICR ON)
Scanning system	Progressive scan
Sync System	Internal
S/N Ratio	50dB
White Balance	AUTO / ATW / INDOOR / OUTDOOR / ONE-CLICK / Manual
Day&Night	Auto, COLOR, B/W (ICR)
Electronic shutter	AUTO / Manual / anti-flicker
AGC	Auto/Manual
Control protocol	SONY VISCA(TTL), bit rate: 9.6 kb/s, 19.2 kb/s, 38.4 kb/s, stop bit: 1/2 optional
BLC	OFF/ BLC/ HLC
Mirror	OFF/ H-Mirror/ V-Mirror/ Rotation

Defog	support (ON/ OFF)
-------	-------------------

2DNR	High/ Middle/Low/OFF
------	----------------------

## LENS

Zoom	20X optical zoom
------	------------------

Focal Length	F=4.7mm~94mm F1.6(W)~F2.8(T)
--------------	------------------------------

Focus	Auto (sensitivity: normal/ low) / Manual / One push
-------	---

Iris	Auto / Manual
------	---------------

## FUNCTION

Network Protocols	HTTP, SMTP, UPnP, DNS, DDNS, NTP, RTSP, RTP, TCP, DHCP, PPPoE
-------------------	---

Dual-stream	Support
-------------	---------

Network Interface	RJ45, support 10M/100M network data
-------------------	-------------------------------------

API	Support software integration open type API, Standard Protocol (Onvif), The third party management platform access
-----	---

Web Browser	Support IE7、IE8、IE9、IE10 and based on the IE core browsers
-------------	--

Smart phone	Support Apple / android system mobile phone to supervise
-------------	--

Horizontal	360° Endless
------------	--------------

Vertical	0°~90° Auto rotation
----------	----------------------

Rotation Speed	Manua: 0.1- 150°/sec, Preset:180°/sec
Preset Accuracy	0.1°
Soft/ hard add	Support
Address	0-255
Preset	256
Pattern	4
Cruise	8
Swing	8
Group	4
continuous Scan	Support
Power up action	Preset / pattem / cruise / group / continuous scan / interval
Home Function	Preset / pattem / cruise / group / continuous scan / interval
IR irradiation distance	100M
IR irradiation angle	Adjustable by zoom
Control interface	RS-485
protocol	Pelco-D/Pelco-P auto identify
Bit rate	2400、4800、9600 auto identify

Alam Input	2 CH input, 1CH output
Alarm Linkage	Preset / pattem / cruise / group / continuous scan / interval
Audio	1 CH input, 1CH output
OSD Menu	English
<b>ENVIRONMENT</b>	
Power supply	DC12V 5A
Power	65W
Operating Temp	-30°C ~60°C
Humidity	0%~90%
Size	415(H)×243(D)mm
Application environment	Outdoor
Water proof	IP66
Weight	10KG

### Dimension:

